

# BallastWise®



## FLUORESCENT BALLAST SPECIFICATIONS

### DESCRIPTION

CATALOG	TYPE	STARTING METHOD	NUMBER OF LAMPS	LAMP TYPE
DXE2H82	Electronic	Instant Start	2	F32T8, F25T8, F17T8

### ELECTRICAL CHARACTERISTICS

INPUT VOLTAGE	LAMP WATTS	INPUT WATTS	INPUT CURRENT	OCV	PF	FREQUENCY	SOUND RATED
277V	32W, 25W, 17W	58W	0.22A	580VRMS	0.98	60HZ	A
MIN START TEMP	CLASS	TYPE	BALLAST FACTOR	BEF	THD(1)	NO PCB'S	
0°F / -18°C	P	1 Outdoor	0.88	1.517	<20%		


### PHYSICAL CHARACTERISTICS

	CASE DIMENSIONS				
	UNITS	M	L	W	H
	INCHES	8.90	9.50	1.70	1.20
	TOL (+/-)	0.05	0.05	0.05	0.05
	LEAD LENGTH				
	UNITS	BLACK	WHITE	RED	BLUE
INCHES	1×16	1×16	1×36	2×24	
TOL (+/-)	+3/8, -0	+3/8, -0	+3/8, -0	+3/8, -0	


### CARTON CHARACTERISTICS

UNITS/CARTON	CARTONS/LAYER	#OF LAYER	UNITS/PALLET	PIECE WEIGHT	CARTON WEIGHT	PALLET WEIGHT
20				1.5 lbs	31.3 lbs	
CARTONS/PALLET	CARTON DIMENSIONS	PALLET DIMENSIONS	PALLET DIMENSIONS LOADED, INCLUDING WOOD PALLET			
	13.2×10.6×6.7					

### PRODUCT PHOTO



### ELECTRICAL DIAGRAM



### PRODUCT LABEL

<h2>Ballast Wise™</h2> <p>ELECTRONIC BALLAST</p> <p>Cat.No: DXE2H82 Type 1 Outdoor Sound Rating: A Start Temp: 0°F-120°F Lamp Type: 2" F32T8, 2" F25T8, 2" F17T8</p>	<p>Input: 277V 60Hz Max Line Current: 0.22A Power Factor &gt;0.98 Line Current THD&lt;20%</p>	LISTED E178684 61FK DEXIN LIGHTING 1-866-4DEXIN8 GOVINA CA91722	
	<p>WARNING: Insulate unused lead(s) for 1000V. Install per National and Local Electrical Codes. Ground Ballast &amp; Mount within 3/4" of ground Metal Reflector.</p>		

