

BallastWise®



FLUORESCENT BALLAST SPECIFICATIONS

DESCRIPTION

CATALOG NO.	TYPE	STARTING METHOD	NUMBER OF LAMPS	LAMP TYPE
DXE3H5UD	Electronic	Program Rapid Start	3	F28T5

ELECTRICAL CHARACTERISTICS

INPUT VOLTAGE	REQUENCY	LAMP WATTS	INPUT WATTS	INPUT CURRENT	THD	PF	SOUND RATED A	
120V / 277V	50/60Hz	28W	93W/91W	0.78A/0.33A	<10%	0.99		
MIN START TEMP	Class P	TYPE 1 Outdoor	BALLAST FACTOR		BEF	O.C.V.	BALLAST FREQUENCY	NO PCB'S
32°F/0°C			1.00	1.075	300VRMS	>40kHz		

PHYSICAL CHARACTERISTICS

	CASE DIMENSIONS						
	UNITS	M	L	W	H		
	INCHES	16.20	16.88	2.25	1.00		
	TOL(+/-)	0.05	0.05	0.05	0.05		
CONNECTOR WIRETRIP							
COLOR	BLACK	WHITE	GREEN	RED	YELLOW	BLUE	BROWN
NUMBER	1	1	1	2	3	4	1

PRODUCT PHOTO

PRODUCT LABEL

	<p>BallastWise™ ELECTRONIC BALLAST</p>	<p>Input: 120 to 277 V 50/60Hz Max. Line Current 120V/0.78A 277V/0.33A Power Factor>0.99 Max. Line Current THD<10%</p>	<p>1-866-433-9468</p>	<p>WARNING</p> <p>Ballast must be grounded Ground to case or input terminal(GRN) Install in accordance with the National Electrical Code</p>	<p>Risk of Electric Shock</p> <ul style="list-style-type: none"> Turn power off before servicing properly ground ballast and fixture <p>Use 18 AWG Solid Copper Wire Rated ≥600V Stripped to 0.33"</p>	
<p>Dimming Range 100%-5% Lamp Current</p>	<p>Cat. No.:DXE3H5UD Sound Rating A</p> <p>Type 1 Outdoor O.C.V.:300VRMS</p> <p>Program Rapid Start Class P</p> <p>Start Temp.:32 F~120 F NO PCB's</p> <p>Lamp Type: 3°F28T5</p>	<p>End of Life Protection Meets FCC Part18 Class A Inherent Thermal Protection Protection Thermiques Integree</p>	<p> LISTED E178684 61FK</p>	<p>DATE:</p>		